

# DTL MiniBlox<sup>TM</sup>

## 4006 Desktop power supply



### Features

- External desktop power supply with locking connector
- IEC320 C14 mains inlet for worldwide operation

### Description

The 4006 External desktop power supply with IEC mains inlet for worldwide operation.

It provides sufficient power for any MiniBlox unit.

[www.miniblox.com](http://www.miniblox.com)

### Specifications

#### Input

Connectors	IEC320 C14
Voltage	90-264VAC
Frequency	47-63Hz
Current	400mA

#### Performance

Efficiency	70% minimum
------------	-------------

#### Output

Connector	Locking connector (2.5mm with +ve centre)
Voltage	6V DC $\pm$ 10%
Current	2A
Ripple & noise	Typically 1%

#### Other

Standards	UL listed & CE marked (IEC 60950)
Temperature range	0°C to 40°C at maximum load
Dimensions	91mm x 38mm x 35mm (excluding cable & connector)
Weight	165g
Safety approvals	All major international standards including CE and UL

We reserve the right to change technical specifications without prior notice. E&OE.

**DTL Broadcast Ltd, Johnson's Estate, Silverdale Road, Hayes, Middlesex, UB3 3BA, UK.**

Phone: +44 (0) 20 8813 5200 Fax: +44 (0) 20 8813 5022 Internet: [www.dtl-broadcast.com](http://www.dtl-broadcast.com) Email: [sales@dtl-broadcast.com](mailto:sales@dtl-broadcast.com)